

QuadGuard™ CEN

Model Number Description with connection panel options

QIXXYC-ZZZ

Where XX represents the system width

24	610 mm	(24")
30	760 mm	(30")
36	915 mm	(36")
69	1753 mm	(69")
90	2286 mm	(90")

Where YY represents the performance level


03	50 km/h (31 mph)	3 bays
05	80 km/h (50 mph)	5 bays
06	100 km/h (62 mph)	6 bays
08	110 km/h (69 mph)	8 bays

Where C represents the nose colour


G	Grey
Y	Yellow
B	Black

Where -ZZZ represents the connection panel(s) provided (if any)


-WL	to W-Beam, left side only
-WR	to W-Beam, right side only
-WLR	to W-Beam, both left and right sides
-TL	to Thrie Beam, left side only
-TR	to Thrie Beam, right side only
-TLR	to Thrie Beam, both left and right sides
-SL	to Safety-shaped barrier, left side only
-SR	to Safety-shaped barrier, right side only
-SLR	to Safety-shaped barrier, both left and right sides
-ESL	to vertical concrete, left side only
-ESR	to vertical concrete, right side only
-ESLR	to vertical concrete, both left and right sides



W – connection to W-Beam



T – connection to Thrie Beam



S – connection to Safety-shaped barrier



ES – connection to vertical concrete